


# Endur i7

**OD-3R**


1200 x 1000 mm



Technical Data	Bottom support	Top Deck	Dimensions (mm)	Maximum Load Capacities (kg)			Weight (kg)		
				Static	Dynamic	Racking	PE	PP	PO
Endur i7 (OD-3R)	3 runners	open	1200 x 1000 x 160	6000	2500	1250	-	20,5	-

Entry: 4 ways | Nesting height: - mm | Safety rim: 7 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40' HC Container	
	per Stack	per Truck	per Stack	per Truck	per Stack	per Truck	per Stack	per Truck	per Stack	per Truck
Endur i7 (OD-3R)	15	390	-	-	17	442	17	476	16	342

**Benefits**

1. Designed to maximize impact resistance
2. Excellent performance in high-rotation usage
3. Exceptional bending strength, ideal for roller conveyors and high rack systems
4. Easy to clean and dry, perfect for semi-hygienic applications
5. Feet with rounded corners to optimize the use with forklifts

**Options**

1. Safety rims
2. Anti-slip strips and grommets on and under deck
3. RFID transponders and other IoT options
4. Specific colors on request
5. Individual marking and labeling
6. ESD: conductive and anti-static